#### LIQUIMOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Turn the engine off, thoroughly spray the parts to be cleaned and allow the agent to take effect for 2 to 3 minutes. Then restart the engine and generously spray the complete area again with the engine running at medium speed. Repeat cleaning in extreme cases.

**Note:** The spray extension can be detached from the spray nozzle, depending on the application area.

Do not use on hot surfaces or polycarbonate. The product may lead to color changes on paints. We therefore recommend covering the areas at risk prior to application. Always test on hidden areas first if using on sensitive materials

## Available pack sizes

| 400 ml Can aerosol | 5111<br>D-GB-I-E-P     |
|--------------------|------------------------|
| 400 ml Can aerosol | 2846<br>GB-DK-FIN-N-S  |
| 400 ml Can aerosol | 7578<br>D-RUS-UA       |
| 400 ml Can aerosol | 8986<br>D-NL-F-GR-ARAB |

Our information is based on thorough research and may be considered reliable, although not legally binding.

# **Product information**Pro-Line Throttle Valve Cleaner

#### Description

Special active solvent for cleaning typical contamination and deposits found in the intake and throttle valve areas. Dissolves and removes all smeary deposits and contaminants such as oil, resins, adhesive residues, etc. Also reliably cleans nozzles and internal components. Ensures the operability of all moving parts and reduces fuel consumption.

#### **Properties**

- excellent cleaning effect
- simple to use
- cleaning possible without dismantling
- optimizes economical use
- rapid cleaning
- tested for catalytic converters

## Technical data

| Density            | 0,87 g/cm³                                    |
|--------------------|---|
| Color / appearance | gelb / yellow                                 |
| Form               | lüssig, aerosol / liquid,<br>aerosol          |
| Base               | Lösungsmittelgemisch /<br>Mixture of solvents |
| Odor               | aromatisch / aromatic                         |
| Flash point        | -19 °C  |

## Areas of application

Removes contamination and deposits in the intake and throttle valve area. Only suitable for use in gasoline engines.

#### Application



Phone: +49 (0)731/1420-13

Fax: +49 (0)731/1420-82

e-mail: info@liqui-moly.de

