

Gear-Oil Leak Stop

Description

Gear Oil Leak Stop is a special combination of active agents formulated for sealing leaky manual, auxiliary and differential transmissions. Cleans seals made from rubber or plastic and seals leaks rapidly and economically.

Properties

- prevents oil spots and pollution of the environment
- increases operational reliability
- optimum lubrication under all operating conditions
- avoids oil leaking onto clutches
- prevents oil loss
- simple to use
- remedies leaks at shrunken or porous seals
- miscible with all commercially available gear oils

Technical data

Viscosity at 40 °C	642 mm ² /s DIN 51562
Viscosity index	101 DIN ISO 2909
Flash point	66 °C DIN ISO 2592
Pour point	-27 °C DIN ISO 3016
Color number (ASTM)	3,5 DIN ISO 2049
Base	Additivkombination / combination of additives
Color / appearance	blau / blue
Density at 20 °C	0,92 g/ml
Odor	charakteristisch / characteristic
Form	flüssig / liquid

Areas of application

For all manual, auxiliary and differential transmissions.

Not suitable for use in automatic transmissions.

Application

One tube is sufficient for 1 litre of gear oil. Use two tubes for large-capacity transmission cases. The product can be added at any time. For best results, add every time the oil is changed.



Available pack sizes

50 ml Tube plastic	1042 D
--------------------	-----------

Our information is based on thorough research and may be considered reliable, although not legally binding.